

# Android Terminal

Home » Newland N910

## Newland N910

### Thin, lightweight, portable smart device

The Newland N910 terminal allows you to run your business from anywhere. The fast, wireless Newland N910 POS device has built-in features to help you serve customers better. Use Newland's apps to manage everything from accounting to customer feedback.

- Compact and ergonomic with a unique non-slip design on the back
- 5MP auto-focus camera with flashlight and able to read 1D/2D codes
- Optional docking stations with charging and multiple peripherals connectivity



### Specifications

OS

**Android 7.1**

CPU

**32-bit ARM Cortex A7 Quad-Core, 1.1GHz + Secure processor, 1GB RAM, 8GB FLASH, 2GB RAM, 16GB FLASH, MicroSD card**

Display

**5-inch TFT full color LCD display, resolution of 1280 x 720, Capacitive multi-touch screen, support electronic signature**

Wireless Communication

**4G / 3G / 2G, WIFI (802.11 b/g/n), Bluetooth 2.1/4.1,**

Positioning

**GPS, GLONASS, BEIDOU**

Magnetic Card Reader

**Triple track, bi-directional, conforming to ISO 7810/7811/7813**

Smart Card Reader

**EMV L1/L2, conforming to ISO 7816, 1.8V/3V/ 5V, synchronous & asynchronous, T=0 & T=1**

Contactless Card Reader

**EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare , Felica**

Camera

**0.3 MP front camera, support 1D/2D code payment, 5 MP autofocus rear camera with flashlight, support 1D/2D code payment**

Fingerprint Reader

**Fast recognized semiconductor fingerprint reader**

Audio

**1 x Speaker, 1 x Microphone, support audio recording and media play**

Keypad

**Secure virtual keypad for PIN entry, 1 x power button, 1 x function key**

Printer

**High-speed thermal printer, 32lps; Paper roll diameter: 40mm, width: 58mm**

Peripheral Ports

**1 x Micro USB (OTG), 1 x DC Jack**

Card Slots

**2 x SIM ,1 x SAM, 1 x SIM ,2 x SAM**

Battery

**Li-ion battery, 7.2V/2600mAh/18.7Wh (Equal to 3.6V/5200mAh)**

Power Supply

**Input: 100-240V AC 50/60Hz, 0.3A, Output: 5.0V DC, 2.0A**

Docking Station

**Charging base, Multi-function base: Charging, Ethernet , Bluetooth, WIFI Access Point, 1 x USB-A, 1 x RS232**

Dimensions

**190mm (L) x 81mm (W) x 54.9mm (H)**

Weight

**440g including battery**

Environment

**Operating temperature: 0°C~40°C (32°F~104°F), Storage temperature: -20°C~60°C (-4°F~140°F), Relative humidity: 5%~93% (Non-condensing)**

Certifications

**PCI PTS 6.x, EMV L1/L2, EMV Contactless L1, PayPass, payWave, American ExpressPay, Discover D-PAS, UnionPay QuickPass, JCB, ATEX, TQM, CE, RoHS**