



Android Terminal

Home » Newland N910 Pro

Newland N910 Pro

Thin, lightweight, portable smart device

The Newland N910 terminal allows you to run your business from anywhere. The fast, wireless Newland N910 POS device has built-in features to help you serve customers better. Use Newland's apps to manage everything from accounting to customer feedback.

- Compact and ergonomic with a unique non-slip design on the back
- 5MP auto-focus camera with flashlight and able to read 1D/2D codes
- Optional docking stations with charging and multiple peripherals connectivity

Specifications

OS

Android 10

Application Processor

Cortex Quad-core A53, 1.4GHz

Security Processor

ARMv7-M security core, 192MHz

Memory

1GB RAM, 8GB FLASH, 2GB RAM, 16GB FLASH, MicroSD card

Display

5.5-inch TFT full color LCD display, resolution of 1280 x 720, with adjustable backlight, Capacitive multi-touch screen, support electronic signature

Wireless Communication

4G / 3G / 2, WIFI (802.11 b/g/n), Bluetooth 2.1/4, WIFI (802.11 a/g/n)

Positioning

GPS, GLONASS, BEIDOU

Magnetic Card Reader

Triple track, bi-directional, conforming to ISO 7810/7811/7813

Smart Card Reader

EMV L1/L2, conforming to ISO 7816, 1.8V/3V/5V, synchronous & asynchronous, T=0 & T=1

Contactless Card Reader

EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare, Felica

Camera

0.3 MP front camera, support 1D/2D code payment, 2 MP front camera, support 1D/2D code payment, 5 MP autofocus rear camera with flashlight, support 1D/2D code payment

Fingerprint Reader

Fast recognized semiconductor fingerprint reader

Audio

1 x Speaker, 1 x Microphone, support audio recording and media playback



Keypad

Secure virtual keypad for PIN entry, 1 x power button, 1 x function key

Printer

High-speed thermal printer, 32lps, Paper roll diameter: 40mm Paper width: 58mm

Peripheral Ports

1 x Type C port

Card Slots

2 x SIM, 1 x SAM, 1 x SD, 1 x SIM, 2 x SAM, 1 x SD

Battery

Li-ion battery, 7.2V/2600mAh/18.7Wh (Equal to 3.6V/5200mAh), Li-ion battery, 7.2V/3300mAh/23.7Wh (Equal to 3.6V/6600mAh)

Power Supply

Input: 100-240V AC 50/60Hz, 0.5A, Output: 5.0V DC, 2.0A

Docking Station

Charging base, Multi-function base: Charging, Ethernet, Bluetooth, WIFI Access Point, 1 x Type-C, 1 x RS232

WL-HUB

RS232 (RJ11), 2 x USB-A, Ethernet (RJ45)

Dimensions

193mm (L) x 81mm (W) x 55mm (H)

Weight

473g including battery

Environment

Operating temperature: 0°C~40°C (32°F~104°F), Storage temperature: -20°C~60°C (-4°F~140°F), Relative humidity: 5%~93% (Non-condensing)

Certifications

PCI PTS 6.x, EMV L1/L2, EMV Contactless L1, PayPass, payWave, American ExpressPay, Discover D-PAS, UnionPay QuickPass, JCB, ATEX, TQM, CE, RoHS