



# Android Terminal

Home » Newland X800

## Newland X800

### Compact Android POS System with inbuilt payments

With a super quick processor and extensive memory footprint, X800 is an ideal solution running a wide variety of payment and business-management applications at the point-of-sale.

- Dedicated merchant and customer displays for seamless interaction
- High-speed transaction processing
- Multiple communication options

### Specifications

OS

**Android 10.x**

Application Processor

**AP: Octa-Core Cortex A53, 1.8GHz, SP: Arm Cortex M3 security core**

Memory

**2GB LPDDR4+16GB eMMC, 3GB LPDDR4+32GB eMMC, MicroSD card slot up to 256GB**

Display

**8-inch portrait IPS display, resolution of 800 x 1280, capacitive multi-touch screen**

Customer Display

**5-inch landscape IPS display, resolution of 800 x 480, capacitive multi-touch screen**

Wireless Communication

**4G / 3G / 2G, Wi-Fi (802.11 a/b/g/n/ac) 2.4G&5G, Bluetooth 2.1 EDR/3.0 HS/4.2 LE**

Positioning

**GPS/BEIDOU/GLONASS/GALILEO/QZSS/SBAS**

Magnetic Card Reader

**Triple track, bi-directional, conforming to ISO 7810/7811/7813**

Smart Card Reader

**EMV L1/L2, conforming to ISO 7816, 1.8V/3V/5V, synchronous & asynchronous, T=0 & T=1**

Contactless Card Reader

**EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare, Felica**

Camera

**2 MP fixed focal front camera, support 1D/2D code payment, 2 MP fixed focal rear camera, support 1D/2D code payment**

Audio

**1x Speaker, 1x Microphone, 1x Audio JACK, support audio recording and media play**



Keypad

**Secure virtual keypad for PIN entry, 1x power button**

Printer

**High-speed thermal printer, 80mm/s Paper roll diameter: 50mm Paper width: 58mm**

Peripheral Ports

**1x Type-C, USB2.0 OTG, Pogo Pins**

Battery

**Li-ion battery, 3.8V/6000mAh/22.8Wh**

Card Slots

**2 x SIM, 1 x SAM, 1 x SD, 1 x SIM, 2 x SAM, 1 x SD**

Power Supply

**Input: 100-240V AC 50/60Hz Output: 5.0V DC, 3A**

Docking Station

**Charging base**

Dimensions

**274.9mm(L)\*123.4mm(W)\*101.6mm(H)**

Weight

**895g including battery**

Expansion HUB

**Wired: RS232 (RJ12 / RJ11), 2 x USB-A, Type-C, Ethernet (RJ45), Wireless: RS232 (RJ12 / RJ11), 2 x USB-A, Type-C, Ethernet (RJ45)**

Environment

**Operating temperature: 0°C~50°C (32°F~122°F), Storage temperature: -20°C~70°C (-4°F~158°F), Relative humidity: 5%~93% (Non-condensing)**

Certifications

**PCI PTS 6.x, EMV L1/L2, EMV Contactless L1, PayPass, payWave, American ExpressPay, Discover D-PAS, UnionPay QuickPass, JCB, TQM, CE, RoHS, CB, FeliCa, MIC, BIS, Rupay, MCCS, Sabe**